#### NASA/TM-2000-209891, Vol. 172



# Technical Report Series on the Boreal Ecosystem-Atmosphere Study (BOREAS)

Forrest G. Hall, Editor

### Volume 172 BOREAS TE-18 Landsat TM Maximum Likelihood Classification Image of the NSA

F.G. Hall and D. Knapp

National Aeronautics and Space Administration

**Goddard Space Flight Center** Greenbelt, Maryland 20771

#### The NASA STI Program Office ... in Profile

Since its founding, NASA has been dedicated to the advancement of aeronautics and space science. The NASA Scientific and Technical Information (STI) Program Office plays a key part in helping NASA maintain this important role.

The NASA STI Program Office is operated by Langley Research Center, the lead center for NASA's scientific and technical information. The NASA STI Program Office provides access to the NASA STI Database, the largest collection of aeronautical and space science STI in the world. The Program Office is also NASA's institutional mechanism for disseminating the results of its research and development activities. These results are published by NASA in the NASA STI Report Series, which includes the following report types:

- TECHNICAL PUBLICATION. Reports of completed research or a major significant phase of research that present the results of NASA programs and include extensive data or theoretical analysis. Includes compilations of significant scientific and technical data and information deemed to be of continuing reference value. NASA's counterpart of peer-reviewed formal professional papers but has less stringent limitations on manuscript length and extent of graphic presentations.
- TECHNICAL MEMORANDUM. Scientific and technical findings that are preliminary or of specialized interest, e.g., quick release reports, working papers, and bibliographies that contain minimal annotation. Does not contain extensive analysis.
- CONTRACTOR REPORT. Scientific and technical findings by NASA-sponsored contractors and grantees.

- CONFERENCE PUBLICATION. Collected papers from scientific and technical conferences, symposia, seminars, or other meetings sponsored or cosponsored by NASA.
- SPECIAL PUBLICATION. Scientific, technical, or historical information from NASA programs, projects, and mission, often concerned with subjects having substantial public interest.
- TECHNICAL TRANSLATION.
   English-language translations of foreign scientific and technical material pertinent to NASA's mission.

Specialized services that complement the STI Program Office's diverse offerings include creating custom thesauri, building customized databases, organizing and publishing research results . . . even providing videos.

For more information about the NASA STI Program Office, see the following:

- Access the NASA STI Program Home Page at http://www.sti.nasa.gov/STI-homepage.html
- E-mail your question via the Internet to help@sti.nasa.gov
- Fax your question to the NASA Access Help Desk at (301) 621-0134
- Telephone the NASA Access Help Desk at (301) 621-0390
- Write to:
   NASA Access Help Desk
   NASA Center for AeroSpace Information
   7121 Standard Drive

Hanover, MD 21076-1320

#### NASA/TM-2000-209891, Vol. 172



## Technical Report Series on the Boreal Ecosystem-Atmosphere Study (BOREAS)

Forrest G. Hall, Editor

# Volume 172 BOREAS TE-18 Landsat TM Maximum Likelihood Classification Image of the NSA

Forrest G. Hall, NASA Goddard Space Flight Center David Knapp, Raytheon ITSS, NASA Goddard Space Flight Center Greenbelt, Maryland

National Aeronautics and Space Administration

**Goddard Space Flight Center** Greenbelt, Maryland 20771

	Available from:	
NIACA Contourfour Armong units of		Notional Tasks: -1 Informed C
NASA Center for AeroSpace Information		National Technical Information Service
7121 Standard Drive		5285 Port Royal Road
Hanover, MD 21076-1320		Springfield, VA 22161
Drica Codo: A17		Dring Code, A10
Price Code: A17		Price Code: A10

## BOREAS TE-18 Landsat TM Maximum Likelihood Classification Image of the NSA

Forrest G. Hall, David Knapp

#### **Summary**

The BOREAS TE-18 team focused its efforts on using remotely sensed data to characterize the successional and disturbance dynamics of the boreal forest for use in carbon modeling. The objective of this classification is to provide the BOREAS investigators with a data product that characterizes the land cover of the NSA. A Landsat-5 TM image from 20-Aug-1988 was used to derive this classification. A standard supervised maximum likelihood classification approach was used to produce this classification. The data are provided in a binary image format file.

Note that some of the data set files on the BOREAS CD-ROMs have been compressed using the Gzip program. See Section 8.2 for details.

#### **Table of Contents**

- 1) Data Set Overview
- 2) Investigator(s)
- 3) Theory of Measurements
- 4) Equipment
- 5) Data Acquisition Methods
- 6) Observations
- 7) Data Description
- 8) Data Organization
- 9) Data Manipulations
- 10) Errors
- 11) Notes
- 12) Application of the Data Set
- 13) Future Modifications and Plans
- 14) Software
- 15) Data Access
- 16) Output Products and Availability
- 17) References
- 18) Glossary of Terms
- 19) List of Acronyms
- 20) Document Information

#### 1. Data Set Overview

#### 1.1 Data Set Identification

BOREAS TE-18 Landsat TM Maximum Likelihood Classification Image of the NSA

#### 1.2 Data Set Introduction

This data set classifies the BOReal Ecosystem-Atmosphere Study (BOREAS) Northern Study Area (NSA) into 11 land cover classes: wet conifer, dry conifer, mixed, deciduous, fen, water, bare soil/disturbed, recent burn, regeneration (young), regeneration (medium), and regeneration (old). This classification was done using a maximum likelihood classifier with training sites.

#### 1.3 Objective/Purpose

This classification was produced for BOREAS investigators who needed a land cover data set with which to compare other measurements. For example, one group used it to compare how CO<sub>2</sub> flux varied with land cover along their aircraft flight path.

#### 1.4 Summary of Parameters

Land cover type

The following classes were identified:

Image Value	Class
1	Conifer (Wet)
2	Conifer (Dry)
3	Mixed (Coniferous and Deciduous)
4	Deciduous
5	Fen
6	Water
7	Disturbed
8	Regeneration (Younger)
9	Regeneration (Medium)
10	Regeneration (Older)
11	Visible Burn

#### 1.5 Discussion

The objective of this classification is to provide the BOREAS investigators with a data product that characterizes the land cover of the NSA. These data can be used for modeling purposes. The technique that was used to produce this classification is a standard maximum likelihood supervised classification. Training fields were selected for various land cover types. Statistics were derived from these training sites and subsequently used to classify the image. Specifically, the PCI programs CSG (signature generator) and MLC (multispectral classifier) were used to classify the image.

#### 1.6 Related Data Sets

BOREAS TE-18 Landsat TM Maximum Likelihood Classification Image of the NSA BOREAS TE-18 Landsat TM Maximum Likelihood Classification Image of the SSA BOREAS TE-18 Landsat TM Physical Classification Image of the SSA

#### 2. Investigators

#### 2.1 Investigator Name and Title

Dr. Forrest Hall Biospheric Sciences Branch NASA Goddard Space Flight Center (GSFC

#### 2.2 Title of Investigation

BOREAS TE-18 Regional Scale Carbon Flux from Modeling and Remote Sensing

#### 2.3 Contact Information

#### Contact 1:

Dr. Forrest G. Hall NASA GSFC Code 923 Greenbelt, MD 20771 (301) 286-2974 (301) 286-0239 (fax) Forrest.G.Hall@gsfc.nasa.gov

#### Contact 2:

David Knapp Raytheon ITSS NASA GSFC Code 923 Greenbelt, MD 20771 (301) 286-1424 (301) 286-0239 (fax) David.Knapp@gsfc.nasa.gov

#### 3. Theory of Measurements

This product was produced for general use by modelers. The objective of this classification is to provide the BOREAS investigators with a data product that characterizes the land cover of the NSA. These data can be used for modeling purposes. The technique that was used to produce this classification is a standard maximum likelihood supervised classification. Training fields were selected for various land cover types. Statistics were derived from these training sites and used to classify the image.

#### 4. Equipment

#### 4.1 Instrument Description

The Landsat-5 Thematic Mapper (TM) sensor system records radiation from the seven bands described in Section 4.2.1. It has a telescope that directs the incoming radiant flux obtained along a scan line through a scan line collector to the visible and near-infrared focal plane, or to the mid-infrared and thermal-infrared cooled focal plane. The detectors for the visible and near-infrared bands (1-4) are four staggered linear arrays, each containing 16 silicon detectors. The two mid-infrared detectors are 16 indium-antimonide cells in a staggered linear array, and the thermal-infrared detector is a four-element array of mercury-cadmium-telluride cells.

#### 4.1.1 Collection Environment

The data that were used to produce this classification were collected by the Landsat-5 TM on 20-Aug-1988. Landsat-5 orbits Earth at an altitude of approximately 705 kilometers.

#### 4.1.2 Source/Platform

Landsat-5 satellite

#### 4.1.3 Source/Platform Mission Objectives

The mission of the Landsat-5 satellite is to measure reflected radiation from Earth's surface at a spatial resolution of 30 meters and to measure the temperature of Earth's surface at a spatial resolution of 120 meters.

#### 4.1.4 Key Variables

- Reflected radiation
- Emitted radiation
- Temperature

#### 4.1.5 Principles of Operation

The TM is a scanning optical sensor operating in the visible and infrared wavelengths. It contains a scan mirror assembly that directly projects the reflected Earth radiation onto detectors arrayed in two focal planes. The TM achieves better imagery resolution, sharper color separation, and greater inflight geometric and radiometric accuracy for seven spectral bands simultaneously than the previous Multispectral Scanner (MSS). Data collected by the sensor are transmitted to Earth-receiving stations for processing.

#### 4.1.6 Sensor/Instrument Measurement Geometry

The TM depends on the forward motion of the spacecraft for the along-track scan and uses a moving mirror assembly to scan in the cross-track direction (perpendicular to the spacecraft). The Instantaneous Field of View (IFOV) for each detector from bands 1-5 and band 7 is equivalent to a 30-m square when projected to the ground; band 6 (the thermal-infrared band) has an IFOV equivalent to a 120-meter square.

#### 4.1.7 Manufacturer of Sensor/Instrument

NASA GSFC

Greenbelt, MD 20771

Hughes Aircraft Corporation Santa Barbara, CA

#### 4.2 Calibration

The internal calibrator, a flex-pivot-mounted shutter assembly, is synchronized with the scan mirror, oscillating at the same 7-Hz frequency. During the turnaround period of the scan mirror, the shutter introduces the calibration source energy and a black direct-current restoration surface into the 100 detector fields of view.

The calibration signals for bands 1-5 and band 7 are derived from three regulated tungsten-filament lamps. The calibration source for band 6 is a blackbody with three temperature selections, commanded from the ground. The method for transmitting radiation to the moving calibration shutter allows the tungsten lamps to provide radiation independently and to contribute proportionately to the illumination of all detectors.

#### 4.2.1 Specifications

The TM sensor is sensitive to the following spectral bands:

Channel	Wavelength (µm)	Primary Use
1	0.451 - 0.521	Coastal water mapping, soil vegetation differentiation, deciduous/coniferous differentiation.
2	0.526 - 0.615	Green reflectance by healthy vegetation.
3	0.622 - 0.699	Chlorophyll absorption for plant species
		differentiation.
4	0.771 - 0.905	Biomass surveys, water body delineation.
5	1.564 - 1.790	Vegetation moisture measurement, Snow cloud differentiation.
6	10.450 - 12.460	Plant heat stress measurement, Other thermal mapping.
7	2.083 - 2.351	Hydrothermal mapping.

Band	Radiometric
	Sensitivity [NE(dP)]*
1	0.8%
2	0.5%
3	0.5%
4	0.5%
5	1.0%
6	0.5 K [NE(dT)]
7	2.4%
Ground IFOV	30 m (bands 1-5, 7)
	120 m (band 6)
Avg. altitude	699.6 km
Data rate	85 Mbps
Quantization levels	256
Orbit angle	8.15 degrees
Orbital nodal period	l 98.88 minutes
Scan width	185 km
Scan angle	14.9 degrees
Image overlap	7.6 %

<sup>\*</sup> N.B. The radiometric sensitivities are the noise-equivalent reflectance differences for the reflective channels expressed as percentages [NE(dP)] and temperature differences for the thermal infrared bands [NE(dT)].

#### 4.2.1.1 Tolerance

The TM channels were designed for a noise equivalent differential represented by the radiometric sensitivity shown in Section 4.2.1.

#### 4.2.2 Frequency of Calibration

The absolute radiometric calibration between bands on both sensors is maintained by using internal calibrators that are physically located between the telescope and the detectors and are sampled at the end of a scan.

#### 4.2.3 Other Calibration Information

Relative within-band radiometric calibration, to reduce "striping," is provided by a scene-based procedure called histogram equalization. The absolute accuracy and relative precision of this calibration scheme assumes that any change in the optics of the primary telescope or the "effective radiance" from the internal calibrator lamps is insignificant in comparison to the changes in detector sensitivity and electronic gain and bias with time and that the scene-dependent sampling is sufficiently precise for the required within-scan destriping from histogram equalization. Each TM reflective band and the internal calibrator lamps were calibrated prior to launch using lamps in integrating spheres that were in turn calibrated against lamps traceable to calibrated National Bureau of Standards lamps. Sometimes the absolute radiometric calibration constants in the "short-term" and "long-term parameters" files used for ground processing have been modified after launch because of inconsistency within or between bands, changes in the inherent dynamic range of the sensors, or a desire to make quantized and calibrated values from one sensor match those from another.

#### 5. Data Acquisition Methods

These data were acquired from the Landsat-5 TM sensor and received from the Canadian Centre for Remote Sensing (CCRS), who purchased it from the Earth Observation Satellite Company (EOSAT). As received from CCRS, the image had been processed from raw telemetry to a systematically corrected product within the CCRS MOSAICS system.

#### 6. Observations

#### 6.1 Data Notes

This imagery was collected on 20-Aug-1988. This scene is Path 33, Row 21 in the Landsat Worldwide Reference System (WRS). The solar elevation angle at the time of image acquisition was 40.1 degrees. The solar azimuth angle was 146 degrees. The radiometric quality of this imagery was acceptable.

#### 6.2 Field Notes

Not applicable.

#### 7. Data Description

#### 7.1 Spatial Characteristics

#### 7.1.1. Spatial Coverage

The image area that was classified covers an area that is approximately 129 km by 86 km and includes areas just west of Thompson, Manitoba. These coordinates are in the BOREAS Grid projection. The corners of the data set are as follows:

Corner	Х	Υ	Longitude	Latitude
Northwest	733.920	654.660	99.067W	56.313N
Northeast	862.920	654.660	97.022W	56.099N
Southwest	733.920	568.260	99.301W	55.549N
Southeast	862.920	568.260	97.294W	55.339N

#### 7.1.2 Spatial Coverage Map

Not available.

#### 7.1.3 Spatial Resolution

Each pixel represents a 30-meter by 30-meter area on the ground.

#### 7.1.4 Projection

The area mapped is projected in the ellipsoidal version of the Albers Equal Area Conic (AEAC) projection. The projection has the following parameters:

```
Datum: North American Datum of 1983 (NAD83)
Ellipsoid: Geodetic Reference System of 1980 (GRS80) or
Worldwide Geodetic System of 1984 (WGS84)
Origin: 111.000°W 51.000°N
Standard Parallels: 52° 30' 00"N
58° 30' 00"N
```

Units of Measure: kilometers

#### 7.1.5 Grid Description

The data are referenced to the projection described in Section 7.1.4.

#### 7.2 Temporal Characteristics

#### 7.2.1 Temporal Coverage

This imagery was collected on 20-Aug-1988. This scene is Path 33, Row 21 in the Landsat Worldwide Reference System (WRS). The solar elevation angle at the time of image acquisition was 43.0 degrees. The solar azimuth angle was 148.8 degrees. The radiometric quality of this imagery was acceptable.

#### 7.2.2 Temporal Coverage Map

Not applicable.

#### 7.2.3 Temporal Resolution

This image was collected at a single point in time and is not multitemporal.

#### 7.3 Data Characteristics

#### 7.3.1. Parameter/Variable

Land cover type.

#### 7.3.2 Variable Description/Definition

In a joint meeting of the Terrestrial Ecosystem (TE) modelers and the Remote Sensing Science (RSS) algorithm developers in Columbia, MD, July 1992, the following land cover classes were identified as necessary inputs to the TE models. This classification was performed using bands 1-5 and band 7 of a Landsat TM scene acquired on 20-Aug-1988.

Pixel Value	Class Name	Class Description
1	Wet Conifer	Wet Conifer is an area that contains coniferous trees, dominated by black spruce (picea mariana) or jack pine (pinus banksiana) growing on peat or poorly drained mineral soils that have a moss (typically sphagnum moss, sphagnum spp.) in conjunction with a herbaceous background. These areas are "non-dry" and will contain only small amounts of lichen on dry moss hummocks.
2	Dry Conifer	Dry Conifer is an area that contains coniferous trees (primarily jack pine) with a lichen (cladina) background. These areas have sandy soils that are well drained. Areas of permafrost supporting conifers with a lichen background are also included in this class.
3	Mixed Deciduous and Coniferous	Mixed Deciduous and Coniferous contains coniferous and aspen/birch (populus tremuloides/betula papyrifera) trees. The composition of this class contains less than 80% of the dominant species.
4	Deciduous	The Deciduous class contains primarily aspen/birch. The composition of this class is generally greater than 80% deciduous trees.

5	Fen	The Fen/Bog class is characterized by areas with a water table very near or at the surface. Fens experience lateral water transport whereas bogs are enclosed landforms experiencing only vertical transport. Fens typically contain sedges, moss, and bog birch associated with sparse to medium dense tamarack (larix laricina) stands. Bogs are usually treeless.
6	Water	Water bodies such as ponds, lakes, and streams.
7	Disturbed	The Disturbed class consists of areas that are dominated by bare soil, recently logged areas, or rock outcrops. This class also includes roads, airports, and urban areas.
8	Regeneration (Young)	Areas that have been logged or burned. Logging is much more frequent in the Southern Study Area (SSA). These areas have usually been regenerating for 3 or 4 years since disturbance. These areas can contain aspen or jack pine replanted following logging.
9	Regeneration (Medium)	Areas that have been burned or in some cases logged. These areas have typically been regrowing for up to 7 or 8 years since the disturbance. These areas are usually immature aspen or jack pine.
10	Regeneration (Older)	Areas that burned and have been regenerating for about 12 to 20 years. These areas are usually mixed with class 4, indicating that the area is becoming recognizable as deciduous vegetation.
11	Recent Burn	Areas that have been burned in the last 5 or 6 years. Distinguishable for their charred sphagnum background, they are usually areas of very intense burn where little or no vegetation survived.

#### 7.3.3 Unit of Measurement

Land Cover type - coded but unitless value.

#### 7.3.4 Data Source

Landsat-5 TM scene on 20-Aug-1988 from the CCRS.Forest cover maps of the area were acquired to identify training fields. These forest cover maps were from Forestry Canada and included species composition for various stands. The scale of the maps is 1:12500. These maps were compiled from aerial photography collected in 1984.

#### 7.3.5 Data Range

Pixel values of 0 to 11, stored as 8-bit integers.

#### 7.4 Sample Data Record

Not applicable for image data.

#### 8. Data Organization

#### 8.1 Data Granularity

The smallest amount of data that can be ordered from these data is the entire data set.

#### 8.2 Data Format

#### 8.2.1 Uncompressed Data Files

NSA classification product contains two files as follows:

- File 1: (80-byte American Standard Code for Information Interchange (ASCII) text records)

  Documentation file
- File 2: (2,880 records of 4,300 bytes each) (1 byte per pixel) Classified image with values from 0 to 11

#### 8.2.2 Compressed CD-ROM Files

On the BOREAS CD-ROMs, file 1 listed above is stored as ASCII text; however, file 2 has been compressed with the Gzip compression program (file name \*.gz). These data have been compressed using gzip version 1.2.4 and the high compression (-9) option (Copyright (C) 1992-1993 Jean-loup Gailly). Gzip (GNU zip) uses the Lempel-Ziv algorithm (Welch, 1994) used in the zip and PKZIP programs. The compressed files may be uncompressed using gzip (-d option) or gunzip. Gzip is available from many Web sites (for example, ftp site prep.ai.mit.edu/pub/gnu/gzip-\*.\*) for a variety of operating systems in both executable and source code form. Versions of the decompression software for various systems are included on the CD-ROMs.

#### 9. Data Manipulations

#### 9.1 Formulae

Not applicable.

#### 9.1.1 Derivation Techniques and Algorithms

The PCI programs CSG and MLC were used to create the needed statistics and the classified image. These programs should be referenced for specific formulae.

#### 9.2 Data Processing Sequence

#### 9.2.1 Data Processing Steps

No preprocessing of the image data was done before the maximum likelihood classification was performed. The raw digital numbers of the imagery were used as input for the classification. BOREAS Information System (BORIS) staff copied the ASCII and compressed the binary files for release on CD-ROM.

#### 9.2.2 Processing Changes

None.

#### 9.3 Calculations

#### 9.3.1 Special Corrections/Adjustments

None.

#### 9.3.2 Calculated Variables

Refer to PCI CSG and MLC programs.

#### 9.4 Graphs and Plots

None.

#### 10. Errors

#### 10.1 Sources of Error

The sources of error in this classification can be attributed to several factors. In many cases, the spectral signature of one feature could be similar to the spectral signature of another feature, resulting in confusion. The similarity in spectral signatures could be the result of similar background components and variations in tree density. Error could also be a result of spectral mixing of various features that fall within a 30-meter pixel.

#### 10.2 Quality Assessment

#### 10.2.1 Data Validation by Source

The imagery was spot checked at various locations, and the image class was compared to the forest cover map. An error assessment was performed on the classification. The BOREAS auxiliary sites were used as ground truth. The location of each auxiliary site was identified on the georeferenced image as a 3- by 3-pixel area. Each of the 9 pixels in these areas represents a test point. Many classes such as disturbed or water, were not represented by the auxiliary sites, and are not represented.

#### 10.2.2 Confidence Level/Accuracy Judgment

Although efforts have been made to make this classification as accurate as possible, there is bound to be some confusion between classes. In some areas, low productivity wet conifer or fen can be confused with the dry conifer, especially in areas of very young jack pine.

#### 10.2.3 Measurement Error for Parameters and Variables

The following tables and statistics were derived in assessing the classification accuracy: Confusion Matrix

Classification											
C	lass	1	2	3	4	5	6	7	8	10	
Truth											
Wet Conif	er(1)	112	12	7	0	8	0	0	0	5	
Dry Conif	er(2)	4	45	20	3	0	0	9	0	0	
Mixed	(3)	0	0	12	6	0	0	0	0	0	
Deciduous	(4)	4	0	5	65	5	0	0	0	2	
Fen	(5)	0	0	0	0	9	0	0	0	0	
Disturbed	(7)	*									
Regen.(Old)(10)*											

<sup>\*</sup> no auxiliary sites available in this class.

Class	% Correct
Wet Conifer	77.8%
Dry Conifer	55.6%
Mixed	66.7%
Deciduous	80.2%
Fen	100.0%
Overall	73.0%

Kappa = 0.633 or 63.3% better than chance agreement (Campbell, 1987).

#### 10.2.4 Additional Quality Assessments

None.

#### 10.2.5 Data Verification by Data Center

This image was viewed to make sure that it matched the product description and appeared to be a classification image of the BOREAS NSA.

#### 11. Notes

#### 11.1 Limitations of the Data

The user should keep in mind that these data are not 100% accurate. There may be errors or differences in class interpretation that might limit the use of these data for certain applications.

#### 11.2 Known Problems With the Data

Clouds in this classification show up in the disturbed class, and cloud shadows show up in the water class. These problems are readily apparent when looking at the imagery that was used to create this classification.

#### 11.3 Usage Guidance

Users should be aware of accuracy limitations as well as problems listed in Section 11.2. Before uncompressing the Gzip files on CD-ROM, be sure that you have enough disk space to hold the uncompressed data files. Then use the appropriate decompression program provided on the CD-ROM for your specific system.

#### 11.4 Other Relevant Information

None.

#### 12. Application of the Data Set

This data set can be used by anyone who wants to get an indication of the distribution of land cover types in the BOREAS NSA. See Section 1.4.

#### 13. Future Modifications and Plans

None.

#### 14. Software

#### 14.1 Software Description

Various proprietary programs in the EASI/PACE image processing software from PCI, Inc., were used to classify the image. Questions related to the specific details of the software written to process this data set should be addressed to David Knapp (see Section 2.3). Gzip (GNU zip) uses the Lempel-Ziv algorithm (Welch, 1994) used in the zip and PKZIP commands.

#### 14.2 Software Access

EASI/PACE is a proprietary software package developed by PCI, Inc. Contact PCI for details.

PCI, Inc. 50 West Wilmot St. Richmond Hill Ontario, Canada L4B 1M5 (905) 764-0614 (905) 764-9604 (fax)

Gzip is available from many Web sites across the Internet (for example, ftp site prep.ai.mit.edu/pub/gnu/gzip-\*.\*) for a variety of operating systems in both executable and source code form. Versions of the decompression software for various systems are included on the CD-ROMs.

#### 15. Data Access

The BOREAS NSA maximum likelihood classification image data set is available from the Earth Observing System Data and Information System (EOSDIS) Oak Ridge National Laboratory (ORNL) Distributed Active Archive Center (DAAC).

#### 15.1 Contact Information

For BOREAS data and documentation please contact:

ORNL DAAC User Services Oak Ridge National Laboratory P.O. Box 2008 MS-6407 Oak Ridge, TN 37831-6407

Phone: (423) 241-3952 Fax: (423) 574-4665

E-mail: ornldaac@ornl.gov or ornl@eos.nasa.gov

#### 15.2 Data Center Identification

Earth Observing System Data and Information System (EOSDIS) Oak Ridge National Laboratory (ORNL) Distributed Active Archive Center (DAAC) for Biogeochemical Dynamics http://www-eosdis.ornl.gov/.

#### 15.3 Procedures for Obtaining Data

Users may obtain data directly through the ORNL DAAC online search and order system [http://www-eosdis.ornl.gov/] and the anonymous FTP site [ftp://www-eosdis.ornl.gov/data/] or by contacting User Services by electronic mail, telephone, fax, letter, or personal visit using the contact information in Section 15.1.

#### 15.4 Data Center Status/Plans

The ORNL DAAC is the primary source for BOREAS field measurement, image, GIS, and hardcopy data products. The BOREAS CD-ROM and data referenced or listed in inventories on the CD-ROM are available from the ORNL DAAC.

#### 16. Output Products and Availability

#### **16.1 Tape Products**

These data can be made available on 8 mm, Digital Archive Tape (DAT), or 9-track tapes at 1600 or 6250 Bytes Per Inch (BPI).

#### 16.2 Film Products

None.

#### **16.3 Other Products**

These data are available on the BOREAS CD-ROM series.

#### 17. References

#### 17.1 Platform/Sensor/Instrument/Data Processing Documentation

PACE Image Analysis Kernal Version 5.2. 1993. PCI Inc. Richmond Hill, Ontario.

Richards, J.A. 1986. Remote Sensing Digital Image Analysis: An Introduction. Springer Verlag.

Welch, T.A. 1984. A Technique for High Performance Data Compression. IEEE Computer, Vol. 17, No. 6, pp. 8-19.

#### 17.2 Journal Articles and Study Reports

Campbell, J.B. 1987. Introduction to Remote Sensing. Guilford Press. p.349.

Newcomer, J., D. Landis, S. Conrad, S. Curd, K. Huemmrich, D. Knapp, A. Morrell, J. Nickeson, A. Papagno, D. Rinker, R. Strub, T. Twine, F. Hall, and P. Sellers, eds. 2000. Collected Data of The Boreal Ecosystem-Atmosphere Study. NASA. CD-ROM.

Sellers, P. and F. Hall. 1994. Boreal Ecosystem-Atmosphere Study: Experiment Plan. Version 1994-3.0, NASA BOREAS Report (EXPLAN 94).

Sellers, P. and F. Hall. 1996. Boreal Ecosystem-Atmosphere Study: Experiment Plan. Version 1996-2.0, NASA BOREAS Report (EXPLAN 96).

Sellers, P., F. Hall, and K.F. Huemmrich. 1996. Boreal Ecosystem-Atmosphere Study: 1994 Operations. NASA BOREAS Report (OPS DOC 94).

Sellers, P., F. Hall, and K.F. Huemmrich. 1997. Boreal Ecosystem-Atmosphere Study: 1996 Operations. NASA BOREAS Report (OPS DOC 96).

Sellers, P., F. Hall, H. Margolis, B. Kelly, D. Baldocchi, G. den Hartog, J. Cihlar, M.G. Ryan, B. Goodison, P. Crill, K.J. Ranson, D. Lettenmaier, and D.E. Wickland. 1995. The boreal ecosystem-atmosphere study (BOREAS): an overview and early results from the 1994 field year. Bulletin of the American Meteorological Society. 76(9):1549-1577.

Sellers, P.J., F.G. Hall, R.D. Kelly, A. Black, D. Baldocchi, J. Berry, M. Ryan, K.J. Ranson, P.M. Crill, D.P. Lettenmaier, H. Margolis, J. Cihlar, J. Newcomer, D. Fitzjarrald, P.G. Jarvis, S.T. Gower, D. Halliwell, D. Williams, B. Goodison, D.E. Wickland, and F.E. Guertin. 1997. BOREAS in 1997: Experiment Overview, Scientific Results and Future Directions. Journal of Geophysical Research 102 (D24): 28,731-28,770.

#### 17.3 Archive/DBMS Usage Documentation None.

#### 18. Glossary of Terms

None.

#### 19. List of Acronyms

AEAC - Albers Equal-Area Conic

ASCII - American Standard Code for Information Interchange

BOREAS - BOReal Ecosystem-Atmosphere Study

BORIS - BOREAS Information System

- Bytes Per Inch

CCRS - Canadian Centre for Remote Sensing CD-ROM - Compact Disk-Read-Only Memory DAAC - Distributed Active Archive Center

DAT - Digital Archive Tape DEM - Digital Elevation Model
EOS - Earth Observing System
EOSAT - Earth Observing Satellite Company

EOSDIS - EOS Data and Information System - Geographic Information System

GMT - Greenwich Mean Time

GRS80 - Geodetic Reference System of 1980

GSFC IFOV - Goddard Space Flight Center - Instantaneous Field of View

MSA - Modeling Sub-Area

MSS - Multispectral Scanner

NAD27 - North American Datum of 1927

NAD83 - North American Datum of 1983

NASA - National Aeronautics and Space Administration

NSA - Northern Study Area
ORNL - Oak Ridge National Laboratory
PANP - Prince Albert National Park
RSS - Remote Sensing Science
SSA - Southern Study Area
TE - Terrestrial Ecology

TE - Terrestrial Ecology TM- Thematic Mapper

URL - Uniform Resource Locator

UTM - Universal Transverse Mercator WGS84 - World Geodetic System of 1984
WRS - Worldwide Reference System WRS WWW

- World Wide Web

#### 20. Document Information

#### **20.1 Document Revision Dates**

Written: 06-Apr-1995 Last Updated: 05-Feb-1999

#### **20.2 Document Review Dates**

BORIS Review: 23-Dec-1997

Science Review:

#### 20.3 Document ID

#### 20.4 Citation

When using these data, please include the following acknowledgment as well as citations of relevant papers in Section 17.2:

These data were classified as a part of investigation TE-18, Principal Investigator F.G. Hall, using Landsat TM data from 20-Aug-1988 at 17:03:41 Greenwich Mean Time. The BOREAS science staff produced this data product. Any publication of these data should acknowledge the source of the data as the Canadian Centre for Remote Sensing (CCRS).

If using data from the BOREAS CD-ROM series, also reference the data as:

Dr. Forrest Hall, "BOREAS TE-18 Regional Scale Carbon Flux from Modeling and Remote Sensing." In Collected Data of The Boreal Ecosystem-Atmosphere Study. Eds. J. Newcomer, D. Landis, S. Conrad, S. Curd, K. Huemmrich, D. Knapp, A. Morrell, J. Nickeson, A. Papagno, D. Rinker, R. Strub, T. Twine, F. Hall, and P. Sellers. CD-ROM. NASA, 2000.

#### Also, cite the BOREAS CD-ROM set as:

Newcomer, J., D. Landis, S. Conrad, S. Curd, K. Huemmrich, D. Knapp, A. Morrell, J. Nickeson, A. Papagno, D. Rinker, R. Strub, T. Twine, F. Hall, and P. Sellers, eds. Collected Data of The Boreal Ecosystem-Atmosphere Study. NASA. CD-ROM. NASA, 2000.

#### 20.5 Document Curator

#### 20.6 Document URL

#### REPORT DOCUMENTATION PAGE

Form Approved OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

1. AGENCY USE ONLY (Leave blank)	2. REPORT DATE October 2000	3. REPORT TYPE AN Technical Men	
4. TITLE AND SUBTITLE Technical Report Series on the Bo BOREAS TE-18 Landsat TM M of the NSA 6. AUTHOR(S) Forrest G. Hall and David Kn	aximum Likelihood Classi	• .	5. FUNDING NUMBERS  923 RTOP: 923-462-33-01
Forrest G. Hall, Editor  7. PERFORMING ORGANIZATION NAME	E(S) AND ADDRESS (ES)		8. PEFORMING ORGANIZATION REPORT NUMBER
Goddard Space Flight Center Greenbelt, Maryland 20771			2000-03136-0
9. SPONSORING / MONITORING AGE National Aeronautics and Space Washington, DC 20546-0001	10. SPONSORING / MONITORING AGENCY REPORT NUMBER TM—2000–209891 Vol. 172		
11. SUPPLEMENTARY NOTES  D. Knapp: Raytheon ITSS, N	ASA Goddard Space Flig	ght Center, Greenl	oelt, Maryland
12a. DISTRIBUTION / AVAILABILITY STA Unclassified—Unlimited Subject Category: 43 Report available from the NASA 7121 Standard Drive, Hanover,	A Center for AeroSpace Info	·	12b. DISTRIBUTION CODE

#### 13. ABSTRACT (Maximum 200 words)

The BOREAS TE-18 team focused its efforts on using remotely sensed data to characterize the successional and disturbance dynamics of the boreal forest for use in carbon modeling. The objective of this classification is to provide the BOREAS investigators with a data product that characterizes the land cover of the NSA. A Landsat-5 TM image from 20-Aug-1988 was used to derive this classification. A standard supervised maximum likelihood classification approach was used to produce this classification. The data are provided in a binary image format file.

14. SUBJECT TERMS BOREAS, terrestrial ecology, Landsat.			15. NUMBER OF PAGES 15 16. PRICE CODE
17. SECURITY CLASSIFICATION OF REPORT Unclassified	18. SECURITY CLASSIFICATION OF THIS PAGE Unclassified	19. SECURITY CLASSIFICATION OF ABSTRACT Unclassified	20. LIMITATION OF ABSTRACT $UL$